

PRESENTATION


SKYLIGHT INTEGRAL WATERLOOP R-290

This information is confidential and was prepared by Epta solely for our internal use. It is not to be relied on by any third party without Epta prior written consent

SKYLIGHT INTEGRAL WATERLOOP R-290







Enter the new generation waterloop system


ABOUT WATERLOOP



What is a waterloop system?



Waterloop system is a <u>cost-effective solution</u> for stores, which allows to <u>connect self contained water condensed refrigeration equipment</u> to <u>glycol-cooled heat rejection loop</u>. Chilled or frozen <u>food heat is captured</u> by Bonnet Névé cooling solutions and <u>rejected into waterloop system</u> through <u>INTEGRAL WATERLOOP device</u>.




ABOUT WATERLOOP



What is a waterloop system?



Waterloop system <u>rejects excess condensation heat</u> through liquid pipes to a dry cooler <u>outside</u> <u>of the building</u> or through an <u>heat recovery</u> exchanger for building and water heating. This solution can be connected to various refrigeration units like <u>multidecks, semi</u> <u>verticals, serve-over counters, freezer cabinets</u> and also <u>coldrooms</u>.



ABOUT WATERLOOP



Main advantages



Waterloop system is an <u>alternative to traditional centralized/remote</u> supermarket refrigeration systems operating with racks of multiple compressors and other components installed in the machinery room, that are connected to a remote condenser and linked to multiple refrigeration display cases in the sales area through a refrigerant piping network.

Major advantages of waterloop system compared to remote solution:

- Energy efficient up to -30%
- Environmental friendly / F Gas compliant
- Lower installation and maintenance costs (copper refrigeration pipes replaced by hydraulic ones)
- Less piping work / faster connection
- Lower total gas charge up to -80%
- Reduced leakage risk up to -96%
- No additional machinery room needed
- Faster store set-up
- Lower power requirement and operating costs
- Lower refrigerant charge per unit
- Reduced carbon footprint
- Easy components replacement
- Easy integration with store heat recovery systems
- One loop only for both medium and low temperature display cases

This information is confidential and was prepared by Epta solely for our internal use. It is not to be relied on by any third party without Epta prior written consent

INTEGRAL WATERLOOP



Product at a glance




INTEGRAL WATERLOOP is a <u>full integrated</u> waterloop solution <u>preassembled</u> on SkyLight cabinet vertical freezer.

INTEGRAL WATERLOOP is powered by last **generation**DC inverter compressor using R-290 (propane) low

GWP refrigerant complaint with normative gas charge of 150 grams per refrigeration circuit.

This new version has been <u>designed to reach high</u> <u>efficiency energy consumption performance</u> and in the meantime to <u>make installation and start up easier</u>.

INTEGRAL WATERLOOP offers a <u>large and flexible</u> range of <u>user friendly</u> cabinets with <u>enhanced</u> modularity adapted to all stores configurations from Hypermarkets to convenience stores.



confidential and was prepared by Epta solely for our internal use. It is not to be relied on by any third party without Epta prior written consent

INTEGRAL WATERLOOP



Product at a glance

Epta

SkyLight INTEGRAL WATERLOOP product range

HEIGHT	Н	20	Н	COMPRESSORS					
DEPTH	EFFICIA	MODULAR	EFFICIA	MODULAR	PER CABINETS				
2D	X	X	X	X	1				
2D EOL		TM		TM	2				
3D	X	X	X	X	2				
3D EOL		X		X	2				
3D-S	N/A	TM		TM	2				
4D	X	X	X	X	2				
5D	N/A				N/A				




Main fetaures:

- Eco friendly natural refrigerant R290
- DC inverter compressor
- Dual circuit evaporator
- High efficiency micro plate condenser
- Smart communicating control
- Easy to install hydraulic options
- 230V / 1 ph / 50 hZ on 2 and 3 doors models



Dimensions – SkyLight Efficia





Models	L (mm)	L (mm)	(Tr.)	o (m²)	o kg	V (dm³)	TDA (m²)
		Glass	Blind		Max	450	450
2P	1562	1664	1664	2,3	-	1218,4	2,3
3P	2343	2445	2445	3,5	-	1827,5	3,5
4P	3124	3226	3226,00	5,0	-	2436,7	4,6


5

This information is confidential and was prepared by Epta solely for our internal use. It is not to be relied on by any third party without Epta prior written consent



Dimensions - SkyLight Modular





L Committee	L (mm)		O (m²)	Q kg	V (dm³)			TDA (m²)		
	Glass	Blind		Max	450	550	600	450	550	600
1562	1664	1664	2,3	-	1265,2	1562,0	1608,9	2,5	2,4	2,3
2343	2445	2445	3,5	1	1897,8	2343,0	2413,3	3,8	3,6	3,5
3124	3226	3226	4,6	1	2530,4	3124,0	3217,7	5,0	4,8	4,6

C


internal use. It is not to be relied on consent

This information is confidential and was prepai by any third party



Dimensions - SkyLight R Efficia





Models	L C	L (mm)		o (m²)	c kg	V (dm²)		TDA (m²)			a south to	
		Glass	Blind		Max	450	550	600	450	550	600	Ē
2P	1562	1664	1664	2,3	-	1265,2	1562,0	1608,9	2,5	2,4	2,3	í
3P	2343	2445	2445	3,5	-	1897,8	2343,0	2413,3	3,8	3,6	3,5	Š
4P	3124	3226	3226	4,6	-	2530,4	3124,0	3217,7	5,0	4,8	4,6	5 .

10


This information is confidential and was prepared by the board, we have internal use. It is not to be relied on by any third party without Epta prior written consent



Dimensions - SkyLight R Modular







* OPTION

Marketing 02/2020

906 - VALUE

937 - ADVANCE

This information is confidential and was prepared by any third party with

PRODUCT OFFER



Additionnal options

Technical:

Controller Dixell XWi70K or Carel IR33






- Self evaporating water tray
 - ➤ 1 per unit on 2D/3D/3DS models
 - > 2 per unit on 4D models




Flat condenser mask 150 mm



Mask height: 256 mm



• Water safety kit (Y filter, Autoflow valve, Air purgin)



Removable top grid for easier condenser cleaning







PRODUCT OFFER




Additionnal options

Epta

Merchandising:


Shelves: 450 / 550 / 600 mm



Ticket holders (shelves & chest): Paper H40, Universal rail, Hermes



Wired basket 200 / 400 mm



Multisolution front glass 300 / 400 mm




Pull out basket 400 mm



- Chest dividers 150 / 370 mm
- Shelves dividers 150 mm





This information is confidential and was prepared by Epta solely for our internal use. It is not to be relied on by any third party without Epta prior written consent

Additionnal options



Lay out:

• 2 doors / 3 doors EOL narrow

Insulated back painted

2445 mm


EOL P6
3 D

P6
P6

906 mm

906 mm

Insulated back





• End wall bumpers integrated or inox



Central end wall positive / negative



www.bonnetneve.com





Epta S.p.A. participates in the ECC programme for: Refrigerated display cabinets (RDO); Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



